



PREMIUM MATERIALS HANDLING RESILIENT

PREMIA Balanced Performance

Premia tires are designed for durable performance. The square footprint provides even wear and increased stability. The combination of advanced compounding and premium natural rubber combines to create a tire that has excellent heat resistance.

Premia is available in a wide range of sizes and special compounds. It's the reliable solution for all your materials handling needs.

PERFORMANCE DEFINED

TIRE LIFE

Trelleborg products guarantee **best in class** performance. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING

Trelleborg is a **leading approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced costs** for our customers.

STABILITY

Trelleborg products are designed to have **large footprints**, maximizing the contact area leading to better stability and even tire wear.

COMFORT

Trelleborg understands the requirements of a **safe working environment**. Our products are designed to reduce vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

PREMIUM MATERIALS HANDLING RESILIENT

PREMIA

Tire Size	Alternative Size	Rim Size	LOC	Tire Dimensions [mm]		Load Capacity [kg]		
				Overall Diameter	Section Width	Static	Forklift trucks up to 25 km/h	
							Load Wheel	Steering Wheel
15x4½-8 *	125/75-8	3.00D-8	•	380	115	1210	1040	800
5.00-8		3.00D-8	•	451	121	1650	1415	1090
16x6-8	150/75-8	4.33R-8	•	412	151	1740	1495	1150
18x7-8	180/70-8	4.33R-8	•	457	146	2490	2145	1650
140/55-9	15x5.5-9	4.00E-09	•	381	130	1360	1170	900
6.00-9		4.00E-09	•	528	142	2190	1885	1450
21x8-9	200/75-9	6.00E-09	•	516	188	3200	2755	2120
6.50-10		5.00F-10	•	571	165	2720	2340	1800
200/50-10		6.50F-10	•	457	194	2870	2470	1900
23x9-10	225/75-10	6.50F-10	•	583	208	4000	3445	2650
7.00-12		5.00S-12	•	657	168	3380	2920	2240
23x10-12	250/60-12	8.00G-12	•	575	230	4380	3770	2900
27x10-12	250/75-12	8.00G-12	•	676	230	4530	3900	3000
7.00-15	29x8-15	5.5-15	•	723	186	4115	3545	2725
8.25-15		6.5-15	•	813	203	5510	4750	3650
28x9-15	225/75-15 (8.15-15)	7.0-15	•	700	206	4530	3900	3000
250-15	250/70-15	7.0-15	•	713	211	5510	4745	3650
250-15	250/70-15	7.5-15	•	713	211	5510	4745	3650
300-15	315/70-15	8.0-15	•	814	241	6795	5850	4500
355/45-15	28x12½-15	9.75-15	•	692	287	6610	5690	4375
355/50-15		9.75-15	•	713	283	6610	5690	4375
355/65-15	32x12½-15 (350-15)	9.75-15	•	818	300	9060	7800	6000

SPECIAL COMPOUNDS AVAILABLE

Non-Marking



Electrically Conductive



High Load



Cut Resistant



Chemical Resistant (Scrubber)

TREAD PATTERNS

Premia



Premia Rib

• Also available with Ribbed tread pattern



WWW.TRELLEBORG.COM/WHEELS