



MID-RANGE MATERIALS HANDLING PNEUMATIC

T-800

Balanced Performance

The T-800 pneumatic tire range has been developed to deliver good performance at a competitive price for forklifts and other industrial equipment. The lug tread pattern provides optimal grip and traction. The cross-ply/diagonal structure ensures high stability and comfort.

PERFORMANCE DEFINED

TIRE LIFE

Trelleborg products guarantee **best in class** performance. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

ENERGY SAVING

Trelleborg is a **leading approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.

STABILITY

Trelleborg tires are designed with **exceptional stability**. Our tires are engineered to ensure **proper distribution of heat** and to prevent excessive deflection under load.

COMFORT

Trelleborg recognizes the importance of a **safe working environment**. Our products are designed to minimize vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

MID-RANGE MATERIALS HANDLING PNEUMATIC

T-800

Tire Size	Alternative Size	Ply Rating	Rim Size	Tire Dimensions [mm]			Inflation Pressure [bar]	Tire Type	Load Capacity [kg]	
				Overall Diameter	Section Width	Tread Depth			Forklift trucks up to 25 km/h	
									Load Wheel	Steering Wheel
15x4½-8	125/75-8	12	3.25-8	385	122	8	10.00	Tube Type	1040	800
5.00-8		10	3.00D-8	465	135	13	10.00	Tube Type	1415	1090
18x7-8	180/70-8	16	4.33R-8	453	160	17	10.00	Tube Type	2145	1650
6.00-9		12	4.00E-09	540	155	13	10.00	Tube Type	1885	1450
21x8-9	200/75-9	14	6.00E-09	536	204	18	9.00	Tube Type	2535	1950
6.50-10		10	5.00F-10	597	183	14	7.80	Tube Type	1950	1500
23x9-10	225/75-10	20	6.50F-10	585	228	19	10.00	Tube Type	3445	2650
7.00-12		14	5.00S-12	685	196	15	9.00	Tube Type	2755	2120
27x10-12	250/75-12	14	8.00G-12	691	245	21	7.00	Tube Type	3545	2725
7.00-15	29x8-15	14	5.5-15	755	190	17	9.30	Tube Type	3250	2500
7.50-15		14	6.0-15	808	215	17	9.30	Tube Type	3640	2800
8.25-15		14	6.5-15	834	255	18	8.00	Tube Type	4225	3250
28x9-15	225/75-15 (8.15-15)	14	7.0-15	722	217	20	10.00	Tube Type	3900	3000
250-15	250/70-15	20	7.0-15	760	240	21	10.30	Tube Type	5040	3875
300-15	315/70-15	20	8.0-15	840	290	25	9.40	Tube Type	6500	5000
28x12½-15	355/45-15	20	9.75-15	728	285	16	9.00	Tube Type	4535	3490
10.00-20	290/95-20	16	8.0-20	1073	278	23	7.90	Tube Type	6500	5000
12.00-20	330/95-20	18	8.0-20	1146	315	25	8.90	Tube Type	8360	6430
12.00-20	330/95-20	22	8.0-20	1146	315	22	10.50	Tube Type	9460	7275
16.00-25*	445/95-25	32	11.25-25/2.0	1493	432	29	10.00	Tubeless	16250	12500
18.00-25*	505/95-25	40	13.00-25/2.5	1675	500	54	10.00	Tubeless	22750	17500
18.00-33*	505/95-33	40	13.00-33/2.5	1875	500	71	10.00	Tubeless	27560	21200

* Tread pattern not shown

TREAD PATTERN

T-800



WWW.TRELLEBORG.COM/WHEELS