



PREMIUM RADIAL INDUSTRIAL PNEUMATIC

## TR-900

### When Only The Best Will Do

The TR-900 is Trelleborg's radial option for industrial applications. Designed to withstand today's demanding applications and modern equipment, the TR-900 offers better stability, traction and security with its unique tread pattern and reinforced sidewalls as compared to a conventional tire.

The TR-900 is ideal for applications with long runs. The radial construction allows for higher speed and a reduced heat build-up which helps to extend the life of the tire.

#### PERFORMANCE DEFINED

##### TIRE LIFE

Trelleborg products guarantee **the best wear** performance in the industry. This results in longer tire life, **additional hours of usage**, reduced downtime and lower maintenance costs.

##### ENERGY SAVING

Trelleborg is a **leading approved tire manufacturer to the OEMs**. We work closely with them to ensure we meet the requirements of energy consumption. This results in **reduced fuel costs** for our customers.

##### STABILITY

Trelleborg tires are designed with **exceptional stability**. Our tires are engineered to ensure **proper distribution of heat** and to prevent excessive deflection under load.

##### COMFORT

Trelleborg recognizes the importance of a **safe working environment**. Our products are designed to minimize vibration and **keep noise to a minimum level**. We follow the strictest regulations for work safety while providing a comfortable ride.

## PREMIUM RADIAL INDUSTRIAL PNEUMATIC

**TR-900**

Tire Size	Alternative Size	Rim Size	Tire Dimensions [mm]			Inflation Pressure [bar]	Tire Type	Load Capacity [kg]	
			Overall Diameter	Section Width	Tread Depth			Forklift trucks up to 25 km/h	
								Load Wheel	Steering Wheel
<b>5.00R8</b>		3.00D-8	468	137	25	10.00	Tube Type	1415	1090
<b>6.00R9</b>		4.00E-09	540	162	25	10.00	Tube Type	1885	1450
<b>6.50R10</b>		5.00F-10	585	180	27	10.00	Tube Type	2340	1800
<b>7.00R12</b>		5.00S-12	670	190	28	10.00	Tube Type	2915	2240
<b>7.00R15</b>	29x8R15	5.5-15	736	195	28	10.00	Tube Type	3540	2725
<b>8.25R15</b>		6.5-15	838	232	32	10.00	Tube Type	4745	3650
<b>28x9R15</b>	225/75R15 (8.15R15)	7.0-15	706	230	25	10.00	Tube Type	4225	3250
<b>250R15</b>	250/70R15	7.0-15	736	252	27	10.00	Tube Type	4745	3650
<b>300R15</b>	315/70R15	8.0-15	835	312	36	10.00	Tube Type	6695	5150
<b>10.00R20</b>	290/95R20	7.5-20	1062	294	35	10.00	Tube Type	6890	5300
<b>12.00R20</b>	330/95R20	8.5-20	1136	320	41	10.00	Tube Type	9230	7100
<b>12.00R24</b>	330/95R24	8.5-24	1232	322	39	10.00	Tube Type	9750	7500
<b>14.00R24</b>	385/95R24	10.0-24	1416	390	64	10.00	Tube Type	14950	11500
<b>16.00R25*</b>	445/95R25	11.25-25/2.0	1495	424	56	10.00	Tubeless	18200	14000
<b>18.00R25</b>	505/95-25	13.00-25/2.5	1636	478	68	10.00	Tubeless	27560	21200
<b>18.00R33</b>	505/95-33	13.00-33/2.5	1838	486	74	10.00	Tubeless	31590	24300

\* Only for use on port applications including straddle carriers and other crane type machinery

**TREAD PATTERNS**

TR-900

TR-900  
16.00R25

WWW.TRELLEBORG.COM/WHEELS